

MATERIALS HEALTH, SAFETY AND ENVIRONMENTAL SHEET
RESIN COATED, KNITTED FIBERGLASS, WATER ACTIVATED REPAIR TAPE
 Prepared 09/30/2006



**PIPE
REPAIR TAPE**

NFPA PLACARD CODE		
HMIS CODE		
Health	2	Moderate
Fire	1	Slight
Reactivity	1	Slight

INGREDIENTS	C.A.S. NO.	PERCENT	EXPOSURE LIMITS
Fiber Glass	65997-17-3	48-52	
4,4' - Diphenylmethane diisocyanate Other MDI isomers and oligomers	101-68-8	34-38	8-hour time weighted average (TWA) 0.005 ppm
Amine catalyst	6425-39-4	1-5	
Methanesulfonic acid	75-75-2	<1	
Ingredients not precisely identified (including Polyethylene glycols) are proprietary and non-hazardous.		<12	

SOURCE OF EXPOSURE LIMIT DATA--ACGIH (American Conference of Governmental Industrial Hygienists)
 THRESHOLD LIMIT VALUES ABBREVIATIONS: N/A - NOT APPLICABLE

Product Name: STOP IT® Repair Tape For Further Information Contact: Telephone Number (713)977-4100	Producer's Name: InduMar Products, Inc. Address: 3355 West Alabama Suite 110 Houston, Texas 77098 Office: (713) 977-4100
--	---

PHYSICAL STATE: Tacky Resin on a Fiberglass Substrate ODOR: Very Slight Flash Back DOES NOT OCCUR. Recommended Extinguishing Media: CO ² , dry chemical or foam	COLOR: White/Yellowish, also Black FLASH POINT: 440° F./227° C. (uncured product) Method: Closed Cup No Unusual Fire or Explosion Hazards. Decomposition/Combustion Products: Carbon dioxide, carbon monoxide and traces of oxides of nitrogen
--	--

Hazardous Polymerization WILL NOT OCCUR. Product will not violently react with air or water.
 Toxic Products will not form. Product is stable, not a hazardous waste.
 Recommended storage conditions: Optimum 40-80° F./4-27° C.

RECOMMENDED WASTE DISPOSAL METHOD: Solid waste landfill or authorized incineration.

PERSONAL PROTECTION: Apply in well ventilated area. Protective clothing for normal application: Latex or plastic gloves. Eye protection for normal application: Safety glasses. Special fire fighting procedures: Wear self-contained breathing apparatus. STOP IT® polyurethane resin will adhere to clothing. STOP IT® polyurethane resin will not cause skin bond.

NOT FOR INTERNAL CONSUMPTION. KEEP AWAY FROM CHILDREN.

HEALTH DATA SHORT TERM EXPOSURE

Route Of Entry	Description of Effect	Minimum Concentration For Effect
Inhalation	No significant inhalation hazard upon removal of cured material. Isocyanate vapors of uncured material below detectable limits.	N/A
Skin	Contact: Modified human draize patch test: Product is neither an irritant nor an allergen. Absorption: Acute dermal LD50 >2.0g./kg., no reaction at this dose. Cured and uncured products are not expected to be sensitizing when used as directed.	N/A
Eyes	Avoid contact; uncured material is not expected to be an irritant when used as directed.	N/A
Ingestion	Oral LD50>5g./kg.; no mortalities, or untoward behavior reactions were noted.	N/A

LONG TERM EFFECTS: May be Slightly irritating to unprotected skin.

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation: Provide fresh air, if breathing becomes difficult, call a physician.
Skin: Wash thoroughly with soap and water.
Eyes: Wash immediately with plenty of water and consult a physician.
Ingestion: Unlikely route. Drink plenty of water. Do not induce vomiting.
Consult a nurse or physician. (Keep out of reach of children).

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on information and tests we believe to be reliable. The accuracy or completeness thereof are not guaranteed. In accordance with "Terms and Conditions of Sale" and since conditions of use are outside our control, the purchaser should determine the suitability of the product for his/her intended use and assumes all risks and liability whatsoever in connection therewith.